

ADVANCE TECH LIQUID LAUNDRY SOUR

National Fire Protection	Fire Ha		Hazardou: Informatio		3
Association (NFPA)	Health 3	O Reactivity	(HMIS)	·	Fire Hazard0Reactivity0
	Specific	Hazard			
Protective Clothing		Emei Over	AND SKIN	CORROSIN BURNS. ED.MAY B	/E. POISON. CAUSES EYE HARMFUL OR FATAL IF E HARMFUL IF ABSORBED
Section 1. Chemica	al Product and	l Company lo	lentification		
Product Name ADVA	NCE TECH LI		RY SOUR	Code	3318621 & 3318639
Product Use Industri	al/Institutional			PMS#	Not available.
MSDS# F-0048	3001			Validation	Date 3/23/2004
U.S. Headquarters		Canadian Head		Print Date	3/23/2004
JohnsonDiversey, Inc. 8310 16th Street		JohnsonDiverse 2401 Bristol Cir	ey - Canada, Inc.	Supersedes	3 /23/2004.
Sturtevant, Wisconsin 531	77-0902	Oakville, Ontari	io L6H 6P1	In Case of	(800) 851-7145
Phone: (888) 352-2249 MSDS Internet Address:		Phone: 1-800-6	68-3131	Emergency	-
www.johnsondiversey.com	ı				
Section 2. Compos	ition and Info	rmation on Ir	ngredients		
Ingredients	CAS#	% by Weight	Exposure Li	mits	LC50/LD50
Fluorosilicic acid	16961-83-4		ACGIH TLV (Unite 2003). Notes: Iden substances ident the BEI documeta Methemoglobin in (for which mether is the principle to and organophosy cholinesterase in are part of this no TWA: 2.5 mg/m ³ OSHA PEL (Unite 1993). Notes: TWA: 2.5 mg/m ³	ntifies ified in ations for nducers moglobin xicity) phorous hibitors ptation. 8 hour(s). d States,	ORAL (LD50): Acute: 430 mg/kg [Rat].
Water	7732-18-5	30-60	Not available.		Not available.

Section 3. Hazards Identification

Routes of Entry

Skin Contact. Eye contact. Inhalation.

Potential Acute Health Effects

Eyes Corrosive. May cause permanent damage including blindness.

JohnsonDiversey	ADVANCE TECH LIQUID LAUNDRY SOUR
	Corrosive. May cause permanent damage. If absorbed through skin, the product can disrupt the body's electrolyte balance by binding essential metal ions such as magnesium and calcium (hypocalcemia) which may disrupt normal heart and nervous system functions. Disruptions to the body's potassium balance (hyperkalemia) may also occur. Effects may appear immediately or be delayed as much as 4 hours after exposure. Death usually results from uncontrollable ventricular fibrillation. Intravenous calcium chloride or gluconate may be indicated to prevent hypocalcemia. Consultation with a medical toxicologist is advised.
	Immediately move the victim to fresh air. Call 911. Inhalation of HF fumes may cause swelling in the respiratory tract up to 24 hours after exposure. Persons who have inhaled HF fumes may need prophylactic oxygen treatment and should be seen by a physician as soon as possible.
	Corrosive. May cause burns to mouth, throat and stomach. If ingested, the product may disrupt the body's electrolyte balance by binding essential metal ions such as magnesium and calcium (hypocalcemia) which may disrupt normal heart and nervous system functions. Disruptions to the body's potassium balance (hyperkalemia) may also occur. Effects may appear immediately or be delayed as much as 4 hours after exposure. Death usually results from uncontrollable ventricular fibrillation. Intravenous calcium chloride or gluconate may be indicated to prevent hypocalcemia. Consultation with a medical toxicologist is advised.
Medical Conditions Aggravated by Overexposure:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.

See Toxicological Information (section 11)

Section 4. First Aid Measures

IF IN CONTACT WITH EYES: Immediately flush eyes for 15 minutes with flowing water. Take the victim to a physician as soon as possible. If possible, apply ice water compresses during transport.
IF ABSORBED THROUGH OR IN CONTACT WITH SKIN: Responders should put on appropriate personal protective equipment to protect themselves before assisting victims. Immediately remove all contaminated clothing. Immediately flush the affected area for five minutes with large amounts of water. While the victim is being rinsed with water, have someone call to arrange medical treatment. If the exposure is to the eyes face, groin, or covers a large area, call 911. For smaller exposure, (i.e. A few drops on the skin), call a physician or poison control center. Immediately after flushing with water start massaging 2.5% calcium glucagon gel into the burn site. Responders must wear gloves when applying the gel to prevent secondary HF burns to their hands. Apply the gel every 15 minutes and massage until pain/redness ceases or professional medical care is available.
IF INHALED: Immediately move the victim to fresh air. Call 911. Inhalation of HF fumes may cause swelling in the respiratory tract up to 24 hours after exposure. Persons who have inhaled HF fumes may need prophylactic oxygen treatment and should be seen by a physician as soon as possible.
IF SWALLOWED- DO NOT induce vomiting. If able to swallow, offer sips of water or milk. GET MEDICAL ATTENTION IMMEDIATELY. Never give anything by mouth to an unconscious person.

Section 5. Fire Fighting Measures

Flammability of the Product	None known.
Flash Points	Open cup: >100°C (212°F) Closed cup: >100°C (212°F).
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).



Section 6. Accidental Release Measures

Personal Precautions Environmental Methods

Put on appropriate personal protective equipment (see Section 8) In the event of major spillage: Use appropriate containment to avoid environmental Precautions and Clean-up contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Wear suitable protective clothing, gloves and eye/face protection. Avoid contact with eyes, skin and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INSTITUTIONAL USE ONLY
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection
	is not required if good ventilation is maintained.

Personal Protection

Eyes Chemical splash goggles.

Hands Chemical resistant gloves.

Respiratory If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Feet Protective footwear.

Body If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Color	Clear.
рН	<1 (Conc. (% w/w): 100) [Acidic.]
Specific Gravity	1.1
Boiling/Condensation	103°C (217.4°F)
Point	
VOC	0 %

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Conditions of Instability	None known.
Incompatibility with Various Substances	Highly reactive with alkalis. Reactive with metals.
Hazardous Decomposition Products	Not available.
Hazardous Polymerization	Will not occur.



Section 11. Toxicological Information		
Acute toxicity	Estimated to be between 500 and 5000 mg/kg (rat).	
Effects of Chronic Exposure	Repeated exposure to high levels of fluoride through ingestion, inhalation, [or dermal absorption- if posing a skin absorption hazard] can cause fluorosis. The primary target is the skeletal system. Effects can include osteoporosis, increased bone density, mottled tooth enamel, and calcification of ligaments.	
Other Toxic Effects	Hydrofluoric Acid (HF) readily penetrates skin, allowing it to destroy soft tissues and decalcify bone. Acute effects of exposure to concentrated (>5%) HF include severe pain, respiratory irritation, severe eye damage, and pulmonary edema. Exposure to less concentrated solutions may have equally serious but delayed effects. Even though HF is chemically defined as a "weak" acid it has a considerable ability to cause severe tissue damage and death. A splash of HF to more than 25% of the body can be fatal and requires immediate medical attention. Death has been reported from contact with strong HF solutions (>50%) to as little as 10% of the body's surface area HF spills contacting the eyes, face, groin and large surface areas of the body require immediate medical attention.	

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information


Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local applicable regulations

Section 14. Transport Information

DOT Classifi	ication	
	Proper ing Name	Please refer to the Bill of Lading/receiving documents for up to date shipping information.
DOT	Class	Not available.
TDG Classif	ication	
TDG	ïcation Proper bing Name	Please refer to the Bill of Lading/receiving documents for up to date shipping information.

Section 15. Regulatory Information

Reporting in this section	on is based on ingredients disclosed in Section 2
US Regulations	
Federal	SARA 302/304/311/312 hazardous chemicals: Fluorosilicic acid SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Fluorosilicic acid
State	New Jersey: Fluorosilicic acid Massachusetts spill list: Fluorosilicic acid Massachusetts RTK: Fluorosilicic acid
	This product is not subject to the reporting requirements under California's Proposition 65.
Registered Product Information	Not applicable.
Canadian Regulations	
WHMIS Classification	Class D-1B: Material causing immediate and serious toxic effects (TOXIC). Class E: Corrosive liquid.



Other Special Not available. Considerations

1.01

Version

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.