

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-PERMATEX
 (877) 376-2839
 Emergency: 800-255-3924 (Chem Tel)
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCTION IDENTIFICATION

Product Name: 95208 NO TOUCH AUTO GLASS STRIPPER 8 FL.OZ
 Item No: GS8-12
 Product Type: Cleaner

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
WATER 7732-18-5	35-45	Not listed	Not listed
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	35-45	Not listed	Not listed
CALCINED DIATOMACEOUS EARTH 91053-39-3	<10	Not listed	Not listed
ALUMINUM OXIDE 1344-28-1	<10	Not listed	15 mg/m ³
ETHYLENE GLYCOL 107-21-1	<5	Not listed	Not listed
BENZENESULFONIC ACID 90218-35-2	<5	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: This product contains ethylene glycol ethers which may be harmful in high concentrations. May cause eye, skin and respiratory irritation. May cause gastrointestinal irritation.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Ingestion may cause nausea and vomiting. Overexposure may cause eye and skin redness. Inhaling may cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ALUMINUM OXIDE 1344-28-1	<10		A4 Not classifiable as a human carcinogen	
ETHYLENE GLYCOL 107-21-1	<5	Male mice-no evidence; female mice-no evidence	A4- not classifiable as a human carcinogen (aerosol)	

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.
Skin contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >212°F
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Firefighters should wear self-contained breathing apparatus.
Hazardous Products of Combustion: Oxides of carbon
Unusual Fire/Explosion Hazards: May ignite when sufficient heat is applied.
Lower Explosive Limit: Not determined.
Upper Explosive Limit: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Absorb spill or leak with sand or cloth. Sweep or shovel into an appropriate waste container until disposal. Flush spill or leak area with water.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).
Handling: Avoid contact with skin and eyes. Do not inhale vapors. Wash thoroughly after handling. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Brown liquid
Odor: Oil-like odor
Boiling Point: 212°F
pH: 6.5
Solubility in Water: Soluble
Specific Gravity: 1.0
VOC(Wt.%): <4% by weight
Vapor Pressure: Not Determined
Vapor Density (Air=1): >1
Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous: Will not occur

Polymerization:
Incompatibilities: Avoid contact with bases and strong oxidizers
Conditions to Avoid: Avoid any source of ignition.
Hazardous Products Oxides of carbon
of Combustion:

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method Disposal should be made in accordance with federal,
of Disposal: state and local regulations.
US EPA Waste Number: NH-Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)
Ground Transport
(DOT)
DOT Shipping Name: Not regulated
Hazard Class: None
UN/ID Number: None
IATA
Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None
IMDG
Proper Shipping: Not regulated
Hazard Class: None
UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313
Toxic Chemical.

ETHYLENE GLYCOL

California Proposition 65: No California Prop 65 chemicals are known to be present.
TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.
Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0
NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:	Denise Boyd, Manger-Environmental, Health & Safety	Revision September 02, 2010 Date:
Company:	Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA 06106	Revision Number: 7
Telephone No.:	1-87-Permatex (877) 376-2839	